1.(twice amended) A communications system

RECEIVEL DEC 20 1959 TC 27:00 MAIL ROOM

comprising:

server;

a server [for] providing information;

a terminal [for] communicating data with the

a communications network [for] connecting said server to said terminal; [and]

a temporary line disconnection [means for] unit, provided in the server and the terminal, monitoring a content of received data from the server and from the terminal, when a specified data is received disconnecting a line being used for data communications without issuing any disconnection notifications to an upper layer application of said terminal and said server when said terminal voice-communicates with a third party other than said server through said communications network during the data communications with said server, and automatically connecting said server to said terminal when the voice communications terminate,

wherein a data communicating process is performed from a status at a point immediately before starting the voice communications when said server and said terminal resume the data communications.

In claim 3, lines 3, 5, 9, please change "means" to -unit--(three places).

In claim 4, lines 3 and 12, please change "means" to --unit--(two places).

In claim 5, line 3, please change "means" to --unit--.

In claim 6, lines 3, 7, and 10, please change "means"

to --unit--(three places).

7. (twice amended) The communications system according to claim 1, further comprising:

an automatic data fetch [means for] unit automatically fetching data from said server to said terminal; and

<u>a</u> storage [means for] <u>unit</u> storing data fetched by said automatic data fetch [means] <u>unit</u>, wherein

said automatic data fetch [means] <u>unit</u>

preliminarily fetches data obtainable from said server and stores the data in said storage [means] <u>unit</u> during the data communications, and accesses said storage [means] <u>unit</u> during the voice communications so that the data in said storage [means] <u>unit</u> is displayed during the voice

B2

communication, thereby realizing virtual data communications during the voice communications.

In claim 8, line 3, please change "means for" to --a unit--.

In claim 8, line 4, please change "means" to --unit--.

In claim 8, line 5, please change "means" to --unit--.

B3

- 9.(twice amended) A communications method comprising the steps of:
- (a) connecting a line from a server to a terminal for providing information for data communications with the server through a communications network; and
- (b) monitoring a content of received data from the server and from the terminal, when a specified data is received disconnecting a line being used for data communications without issuing any disconnection notifications to an upper layer application of said terminal and said server when said terminal voice-communicates with a third party other than said server through said communications network during the data communications with said server, and automatically